

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 07.08.2023

Version number: 1.06

Revision: 02.08.2023

SECTION 1: Identification of the substance/mixture

- **1.1 Product identifier** For Industrial and Professional use only.
- **Trade name:** Acrythane SC601 Colours
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** Surface Coating
- **Application of the substance / the mixture** Surface Coating

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
 - Flam. Liq. 3 H226 Flammable liquid and vapour.
 - Skin Irrit. 2 H315 Causes skin irritation.
 - Eye Irrit. 2 H319 Causes serious eye irritation.
 - STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
 - The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Warning
- **Hazard-determining components of labelling:**
 - XYLENE (Reaction mass of [ortho-xylene, meta-xylene, para-xylene & Ethylbenzene])
- **Hazard statements**
 - H226 Flammable liquid and vapour.
 - H315 Causes skin irritation.
 - H319 Causes serious eye irritation.
 - H373 May cause damage to the hearing organs through prolonged or repeated exposure.
- **Precautionary statements**
 - P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 - P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.08.2023

Version number: 1.06

Revision: 02.08.2023

Trade name: Acrythane SC601 Colours

(Contd. of page 1)

- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-XXXX	Butyl ethanoate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	>10-≤25%
EC number: 905-588-0 Reg.nr.: 01-2119488216-32 01-2119539452-40	XYLENE (Reaction mass of [ortho-xylene, meta-xylene, para-xylene & Ethylbenzene]) ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	>10-≤25%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	>10-≤25%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	Xylene (mix) ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	>2.5-≤10%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35-xxxx	Solvent naphtha (petroleum), light aromatic ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336	>1-≤2.5%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332	>1-≤2.5%
	Polyurethane ⚠ Skin Irrit. 2, H315	>1-≤2.5%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
In case of unconsciousness place patient stably in side position for transportation.
Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing.
Immediately rinse with water.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 07.08.2023

Version number: 1.06

Revision: 02.08.2023

Trade name: Acrythane SC601 Colours

(Contd. of page 2)

- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
Do not induce vomiting; call for medical help immediately and show safety datasheet or label.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Prevent seepage into sewage system, workpits and cellars.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep receptacles tightly sealed.
Ensure good ventilation/extraction at the workplace.
Prevent formation of aerosols.
Hygiene measures:
Wash hands before breaks and at the end of workday.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed and in a well-ventilated place.
Keep away from heat.

(Contd. on page 4)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 07.08.2023

Version number: 1.06

Revision: 02.08.2023

Trade name: Acrythane SC601 Colours

(Contd. of page 3)

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters
- Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

123-86-4 Butyl ethanoate

WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
-----	---

108-65-6 2-methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
-----	--

1330-20-7 Xylene (mix)

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	--

Solvent naphtha (petroleum), light aromatic

OEL	Long-term value: 100 mg/m ³
-----	--

100-41-4 ethylbenzene

WEL	Short-term value: 552 mg/m ³ , 125 ppm Long-term value: 441 mg/m ³ , 100 ppm Sk
-----	---

· DNELs

123-86-4 Butyl ethanoate

Oral	DNEL	2 mg/day (Con)
Dermal	DNEL	6 mg/day (Con)
		11 mg/day (Ind)
Inhalative	DNEL	35.7 mg/m ³ (Con)
		300 mg/m ³ (Ind)

XYLENE (Reaction mass of [ortho-xylene, meta-xylene, para-xylene & Ethylbenzene])

Oral	DNEL	1.6 mg/day (Con)
Dermal	DNEL	108 mg/day (Con)
		180 mg/day (Ind)
Inhalative	DNEL	14.8 mg/m ³ (Con)
		77 mg/m ³ (Ind)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	DNEL	1.67 mg/day (Con)
Dermal	DNEL	54.8 mg/day (Con)
		153.5 mg/day (Ind)
Inhalative	DNEL	33 mg/m ³ (Con)
		275 mg/m ³ (Ind)

1330-20-7 Xylene (mix)

Dermal	DNEL	108 mg/day (Con)
		180 mg/day (Ind)
Inhalative	DNEL	14.8 mg/m ³ (Con)
		77 mg/m ³ (Ind)

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 07.08.2023

Version number: 1.06

Revision: 02.08.2023

Trade name: Acrythane SC601 Colours

(Contd. of page 4)

Solvent naphtha (petroleum), light aromatic

Oral	DNEL	11 mg/day (Con)
Dermal	DNEL	11 mg/day (Con)
		25 mg/day (Ind)
Inhalative	DNEL	32 mg/m ³ (Con)
		150 mg/m ³ (Ind)

· PNECs

CAS No. 1330-20-7 Xylene mixed isomers

- Fresh water; 0.327 mg/l
- Marine water; 0.327 mg/l
- Intermittent release; 0.327 mg/l
- STP; 6.58 mg/l
- Sediment (Freshwater); 12.46 mg/kg
- Sediment (Marinewater); 12.46 mg/kg
- Soil; 2.31 mg/kg

CAS No. 123-86-4 Butyl Acetate

- Freshwater: 0.18 mg/l
- Marine water: 0.018 mg/l
- Fresh water sediment: 0.981 mg/kg
- Marine sediment: 0.0981 mg/kg
- Soil: 0.0903 mg/kg
- STP (sewage-treatment plant): 35.6 mg/l
- Intermittent use/release: 0.36 mg/l

· Ingredients with biological limit values:**1330-20-7 Xylene (mix)**

BMGV	650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid

· Additional information: The lists valid during the making were used as basis.**· 8.2 Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

· Respiratory protection: When spraying the product, use a respiratory protective device.**· Protection of hands:**

When skin exposure may occur, advice should be sought from the glove supplier on appropriate types and usage times for this product.



Protective gloves

· Eye protection:

Tightly sealed goggles

GB

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 07.08.2023

Version number: 1.06

Revision: 02.08.2023

Trade name: Acrythane SC601 Colours

(Contd. of page 5)

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Liquid
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· Melting point/freezing point:	Undetermined.
· Initial boiling point and boiling range:	126 °C

· **Flash point:** 24 °C

· **Flammability (solid, gas):** Flammable.

· **Ignition temperature:** 315 °C

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

· Lower:	1.2 Vol %
· Upper:	10.8 Vol %

· **Vapour pressure at 20 °C:** 11.2 hPa

· Density at 20 °C:	1.023 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.

· **Solubility in / Miscibility with water:** NOT MISCIBLE

· **Partition coefficient: n-octanol/water:** Not determined.

· **Viscosity:**

· Dynamic at 20 °C:	350 mPas
· Kinematic:	Not determined.

· **Solvent content:**

· **Organic solvents:** 44.4 %

· **Solids content:** 55.6 %

· **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

· **10.2 Chemical stability**

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions** No dangerous reactions known.

· **10.4 Conditions to avoid** No further relevant information available.

· **10.5 Incompatible materials:** No further relevant information available.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 07.08.2023

Version number: 1.06

Revision: 02.08.2023

Trade name: Acrythane SC601 Colours

(Contd. of page 6)

- **10.6 Hazardous decomposition products:**
No dangerous decomposition products when stored and handled correctly

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

123-86-4 Butyl ethanoate

Oral	LD50	10,760 mg/kg (rat)
Dermal	LD50	14,112 mg/kg (Rab)
Inhalative	LC50/4 h	23.4 mg/l (Rat)

XYLENE (Reaction mass of [ortho-xylene, meta-xylene, para-xylene & Ethylbenzene])

Oral	LD50	4,300 mg/kg (Rat)
Dermal	LD50	>4,200 mg/kg (Rab)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (Rat)
Inhalative	LC50/4 h	>10.8 mg/l (Rat)

1330-20-7 Xylene (mix)

Oral	LD50	5,000 mg/kg (Rat)
Dermal	LD50	2,000 mg/kg (rbt)
Inhalative	LC50/4 h	11 mg/l (Rat)

Solvent naphtha (petroleum), light aromatic

Oral	LD50	3,492 mg/kg (rat)
Dermal	LD50	3,160 mg/kg (Rab)
Inhalative	LC50/4 h	>6.193 mg/l (rat)

100-41-4 ethylbenzene

Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rbt)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure**
May cause damage to the hearing organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:**
Acute Fish toxicity
Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 07.08.2023

Version number: 1.06

Revision: 02.08.2023

Trade name: Acrythane SC601 Colours

(Contd. of page 7)

LC50 9.22 mg/l

Species: *Oncorhynchus mykiss* (rainbow trout)

Exposure duration: 96 h

Acute toxicity for daphnia

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)

EC50 6.14 mg/l

Species: *Daphnia magna* (Water flea)

Exposure duration: 48 h

Acute toxicity for algae

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)

ErC50 2.9 mg/l

Species: *Pseudokirchneriella subcapitata* (green algae)

Exposure duration: 72 h

Acute bacterial toxicity

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)

EC50 1 - 10 mg/l

Ecotoxicology Assessment

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)

Chronic aquatic toxicity: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Data based on the safety data sheet (SDS) by the supplier.

Acute Fish toxicity

n-Butyl acetate

LC50 18 mg/l

Species: *Pimephales promelas* (fathead minnow)

Exposure duration: 96 h

Chronic Fish toxicity

n-Butyl acetate

No data available.

Acute toxicity for daphnia

n-Butyl acetate

EC50 44 mg/l

Species: *Daphnia* (water flea)

Exposure duration: 48 h

Chronic toxicity to daphnia

n-Butyl acetate

NOEC 23 mg/l

Species: *Daphnia magna* (Water flea)

Exposure duration: 21 d

Method: OECD Test Guideline 211

Acute toxicity for algae

n-Butyl acetate

EC50 675 mg/l

Species: *Scenedesmus quadricauda* (Green algae)

Exposure duration: 72 h

Acute bacterial toxicity

EC50 356 mg/l

Species: activated sludge

Exposure duration: 40 h

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 07.08.2023

Version number: 1.06

Revision: 02.08.2023

Trade name: **Acrythane SC601 Colours**


(Contd. of page 8)

- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---|--|
| · 14.1 UN-Number
· ADR, IMDG, IATA | UN1263 |
| · 14.2 UN proper shipping name
· ADR
· IMDG, IATA | 1263 PAINT RELATED MATERIAL
PAINT RELATED MATERIAL |
| · 14.3 Transport hazard class(es)
· ADR, IMDG, IATA | |
|  | |
| · Class
· Label | 3 Flammable liquids.
3 |
| · 14.4 Packing group
· ADR, IMDG, IATA | III |
| · 14.5 Environmental hazards:
· Marine pollutant: | No |
| · 14.6 Special precautions for user
· Hazard identification number (Kemler code):
· EMS Number:
· Stowage Category | Warning: Flammable liquids.
30
F-E, S-E
A |
| · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · ADR
· Limited quantities (LQ)
· Excepted quantities (EQ) | 5L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml |

(Contd. on page 10)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 07.08.2023

Version number: 1.06

Revision: 02.08.2023

Trade name: Acrythane SC601 Colours

(Contd. of page 9)

· Transport category	3
· Tunnel restriction code	D/E
<hr/>	
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, III

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
 - **Directive 2012/18/EU**
 - **Named dangerous substances - ANNEX I** None of the ingredients is listed.
 - **Seveso category P5c** FLAMMABLE LIQUIDS
 - **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
 - **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
 - **National regulations:**
 - **Technical instructions (air):**
- | Class | Share in % |
|-------|------------|
| NK | 44.4 |
- **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
 - **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Full text of H-Statements referred to under sections 2 and 3:**
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
- **Department issuing SDS:** Product safety department: LABORATORY
- **Contact:** Health & Safety Officer
- **Abbreviations and acronyms:**
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 07.08.2023

Version number: 1.06

Revision: 02.08.2023

Trade name: Acrythane SC601 Colours

(Contd. of page 10)

*CAS: Chemical Abstracts Service (division of the American Chemical Society)**DNEL: Derived No-Effect Level (UK REACH)**PNEC: Predicted No-Effect Concentration (UK REACH)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**Flam. Liq. 2: Flammable liquids – Category 2**Flam. Liq. 3: Flammable liquids – Category 3**Acute Tox. 4: Acute toxicity – Category 4**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Irrit. 2: Serious eye damage/eye irritation – Category 2**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2**Asp. Tox. 1: Aspiration hazard – Category 1**Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3***· * Data compared to the previous version altered.**

GB